



Server



Benutzer



Netzwerk



Codecs



Zertifikate



Sound

- Opus, 18 kbps ^
- G.711 A-Law, 64 kbps
- G.711 u-Law, 64 kbps
- GSM, 13 kbps
- G.722 WB, 64 kbps
- DTMF (RFC4733), - kbps
- DTMF (INFO), - kbps
- G.726-32, 32 kbps
- iLBC, 15 kbps
- Speex, 15 kbps
- Speex WB, 30 kbps
- G.729, 8 kbps
- G.726-16, 16 kbps
- G.726-24, 24 kbps
- G.726-40, 40 kbps
- LinPCM, 705 kbps
- LinPCM-16k, 256 kbps
- Comfort Noise, - kbps v



Echo Unterdrückung

0 ms



500 ms

keine Stille-Erkennung v

MOH: Für Elise v

 SRTP SAVP ZRTP G.726 AAL2

Lokaler Port

5160

+

-

bevorzugte Verbindungsart

UDP

TCP

TLS

PRACK

Session Timers

Multicast DNS

UPnP NAT

IPv6

QoS

CTI: automatische Rufannahme

Windows
Firewall

Dual-Stack

GRUU

Proxy/Registrar

tel.t-online.de

Registrierung

MWI

Registrierungsintervall

900



STUN Server

stun.t-online.de

Domain/Realm

tel.t-online.de

Empfang

Automatische Verstärkungsregelung (AGC)

Rauschunterdrückung



lokales DTMF-Feedback

Versand

Automatische Verstärkungsregelung (AGC)

Rauschunterdrückung

